# **Potassium Dichromate**

### MSDS # 564.00

Section 1:

CANUTEC (Canada): 613-424-6666

Page 1 of 2

# **Product and Company Identification**

### **Potassium Dichromate**

### Synonyms/General Names: Potassium Bichromate.

Product Use: For educational use only

Manufacturer: Columbus Chemical Industries, Inc., Columbus, WI 53925.

24 Hour Emergency Information Telephone Numbers

### CHEMTREC (USA): 800-424-9300

ScholAR Chemistry; 5100 W. Henrietta Rd, Rochester, NY 14586; (866) 260-0501; www.Scholarchemistry.com

Hazards Identification
HMIS (0 to 4)
Health 4
on and known carcinogen, strong oxidizing agent, and body Fire Hazard 0
Reactivity 3
C

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Section 3:	Composition / Information on Ingredients	

Potassium Dichromate (7778-50-9), >99%

Section 4:	First Aid Measures
	Always seek professional medical attention after first aid measures are provided.
Eyes:	Immediately flush eyes with excess water for 15 minutes, lifting lower and upper eyelids occasionally.
Skin:	Immediately flush skin with excess water for 15 minutes while removing contaminated clothing.
Ingestion:	Call Poison Control immediately. Rinse mouth with cold water. Give victim 1-2 cups of water or milk to drink.
-	Induce vomiting immediately.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration.

. . . . . .

## Section 5:

# **Fire Fighting Measures**

Strong Oxidizer. When heated to decomposition, emits acrid chromium oxide fumes.
Protective equipment and precautions for firefighters: Use foam or dry chemical to extinguish fire.
Firefighters should wear full fire fighting turn-out gear and respiratory protection (SCBA). Cool container with water spray. Material is not sensitive to mechanical impact or static discharge.

# Section 6:

## **Accidental Release Measures**

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Sweep up spill and place in sealed bag or container for disposal. Wash spill area after pickup is complete. See Section 13 for disposal information.

## Section 7:

## **Handling and Storage**

Blue

Handling: Use with adequate ventilation and do not breathe dust or vapor. Avoid contact with skin, eyes, or clothing. Wash hands thoroughly after handling.

**Storage**: Store in Toxic Storage Area [Blue Storage] with other toxic material. Store in a dedicated poison cabinet. Store in a cool, dry, well-ventilated, locked store room away from incompatible materials.

# Section 8: Exposure Controls / Personal Protection

Use ventilation to keep airborne concentrations below exposure limits. Have approved eyewash facility, safety shower, and fire extinguishers readily available. Wear chemical splash goggles and chemical resistant clothing such as gloves and aprons. Wash hands thoroughly after handling material and before eating or drinking. Use NIOSH-approved respirator with a dust cartridge. Exposure guidelines: Chromium compounds: OSHA PEL: 0.001 mg/m<sup>3</sup>, ACGIH: TLV: 0.01 mg/m<sup>3</sup>, STEL: 0.1 mg/m<sup>3</sup>.

#### Section 9:

# **Physical and Chemical Properties**

Molecular formula	$K_2Cr_2O_{7.}$	Appearance	Orange-red crystals.
Molecular weight	294.19.	Odor	No odor.
Specific Gravity	2.676 g/mL @ 20°C.	Odor Threshold	N/A.
Vapor Density (air=1)	N/A.	Solubility	Soluble in water, not alcohol.
Melting Point	398°C.	<b>Evaporation rate</b>	N/A. (Butyl acetate = 1).
<b>Boiling Point/Range</b>	N/A.	<b>Partition Coefficient</b>	N/A. $(log P_{OW})$ .
Vapor Pressure (20°C)	N/A.	рН	N/A.
Flash Point:	N/A.	LEL	N/A.
Autoignition Temp.:	N/A.	UEL	N/A.
			N/A = Not available or applicable

### Section 10:

### **Stability and Reactivity**

**Stability:** Stable under normal conditions of use and storage. Avoid heat and ignition sources. **Incompatibility:** Organic materials, oils, grease or any easily oxidizable materials. **Shelf life:** Indefinite if stored properly.

### Section 11:

# **Toxicology Information**

Acute Symptoms/Signs of exposure: *Eyes*: Redness, tearing, itching, burning, conjunctivitis. *Skin*: Redness, itching. *Ingestion*: Irritation and burning sensations of mouth and throat, nausea, vomiting and abdominal pain. *Inhalation*: Irritation of mucous membranes, coughing, wheezing, shortness of breath,

Chronic Effects: Carcinogen, IARC group 1; ACGIH A1, NTP Known

Sensitization: none expected

Potassium Dichromate: LD50 [oral, rat]; 25 mg/kg; LC50 [rat]; N/A; LD50 Dermal [rabbit]; N/A

Material has been found to be a carcinogen or produce genetic, reproductive, or developmental effects.

#### Section 12:

### **Ecological Information**

**Ecotoxicity (aquatic and terrestrial):** not release to environment.

Contains a heavy metal - toxic to terrestrial and aquatic plants and animals. Do

#### Section 13:

# **Disposal Considerations**

Check with all applicable local, regional, and national laws and regulations. Local regulations may be more stringent than regional or national regulations. Use a licensed chemical waste disposal firm for proper disposal.

Section 14:	Transport Information			
DOT Shipping Name:	Oxidizing solid, n.o.s.,	Canada TDG:	Oxidizing solid, n.o.s.	
	(Potassium Dichromate).		(Potassium Dichromate).	
DOT Hazard Class:	5.1, pg II.	Hazard Class:	5.1, pg II.	
Identification Number:	UN1479.	UN Number:	UN1479.	

**Regulatory Information** 

### Section 15:

**EINECS:** Listed (231-906-6) **TSCA:** All components are listed or are exempt WHMIS Canada: C,D1A,D2A, D2B;Oxidizer, toxic material, carcinogen California Proposition 65: Listed Carcinogen.

The product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

### Section 16:

### **Other Information**

#### Current Issue Date: January 23, 2009

Disclaimer: Scholar Chemistry and Columbus Chemical Industries, Inc., ("S&C") believes that the information herein is factual but is not intended to be all inclusive. The information relates only to the specific material designated and does not relate to its use in combination with other materials or its use as to any particular process. Because safety standards and regulations are subject to change and because S&C has no continuing control over the material, those handling, storing or using the material should satisfy themselves that they have current information regarding the particular way the material is handled, stored or used and that the same is done in accordance with federal, state and local law. S&C makes no warranty, expressed or implied, including (without limitation) warranties with respect to the completeness or continuing accuracy of the information contained herein or with respect to fitness for any particular use.